



compac

SPAIN



Wax / fungicide applicator



## Brushes machine with wax or fungicide applicator

Brushes machine designed with a rotation system that allows the product application all around the fruit using rotors or nozzles.

All our models incorporate motorized fruit sweeper, lower scrapers for cleaning the brushes and lower trays for waste collection.

### FEATURES & BENEFITS

- It can be manufactured with a bypass system, which allows to choose whether to wash or brush the fruit through brushes or to pass it through a belt conveyor installed in the same machine, which can be raised or lowered by a spindle lift. We also have a bypass system with 2 separate brush beds.
- Highest quality standards to ensure long durability.



Interior of a brushes machine with applicator

## KEY SPECIFICATIONS

- Designed to comply with the Machine Directive of the European Union (CE) 2006/42/CE
- Maximum capacity according to machine width and type of fruit. Consult.
- Standard widths (mm):  
500 / 750 / 1000 / 1250 / 1500 / 1750 / 2000
- Standard lengths (brushes):  
8 / 12 / 16. Other lengths consult.

Usually the applicators are manufactured for brushes machines of 8 or 12 bars, however they can be installed in a longer brush machine with more type of treatments or drying equipments.



## TECHNICAL INFORMATION

- Power: 3 phases - 380 V - 50 Hz
- Power consumption (brush machine):  
Widths 500-750, 1'13 KW  
Widths 1000-1500, 1'50 KW  
Widths 1750-2000, 1'88 KW

Product applicator (0'37 KW), mixing tank (0'37 KW), by-pass lift system (1'13 KW)



Product applicator in operation



Plant and side view for a 1 meter wide brush machine with applicator.